

EVOLine® Multimedia Modules






**EVOLine® VGA cable**  
**EVOLine® DVI-A cable**

**EVOLine® DVI-D cable**

**EVOLine® HDMI cable**

**Cable properties**




|                     |   |   |  |
|---------------------|---|---|--|
|                     |  |  |  |
| Flame retardant     | self extinguishing  |   | VW-1   |
| Halogen free        | yes   | yes   | yes  |
| Colour              | Black   | Black   |  |
| Outer diameter      | 7,2 mm Ø ± 0,3 mm   | 6,2 mm Ø ± 0,19 mm  | (3.00 ± 0,15)*(13.00 ± 0,30)mm   |
| Bend radius         | 72 mm   | 62 mm ± 0,19 mm   | 28 x 5M  |
| Attenuation         | f (MHz)      dB/100 m   |   | f (MHz)      db/100 m  |
|                     | 100            14,5   |   |  |
| Resistance          | 75 Ω  |   | 100±10Ω  |
| Transmission length | see matrix on page 288  | upto Approx. 15 m   | ca. 25 m   |
| Temperature         | -20° bis 70° C  |   | 80°  |
| Conductors/Coax     | 3   |   |  |
| Conductor section   | 3 x 0,51 mm Ø Cu-wire   | 28 AWG  |  |
| Insulation          | Natural colour with identification threads: Red, Green, Black                     |   |  |
| Shielding           | Single Copper braid   | foil + braid  |  |
| Single core         | 1   |   |  |
| Conductor section   | 1 x 0,4 mm Ø verz. Cu-wire  |   |  |
| Insulation          | Natural colour with identification threads: yellow                                |   |  |
| Shielding           | metal laminated foil  |   |  |
| Cores               | 6   | twisted pair  |  |
| Leads               | 2 x 3 x 0,08 mm Ø verz. Cu-braid  | 4x 0,38 mm, 5 x 0,127 mm  |  |

Very high quality cable, that by its construction, transfers the bandwidth (Frequency) of the entire VGA mode. Three 75 Ω Coaxial cores, the RGB signals with no visible Propagation delays transferred. Six control cores are under others for transmission of the DDC mode and the hardware detect. High transmission quality is ensured by extremely low attenuation structure of the Coaxial cores, combined with a optimal synchronization factor. Optimal sizing of cables for H-/V-Synchronous impulses. Flame retardant and halogen free. Cable meets the Requirement of public authority and industry.

Highgrade twisted pair Cable, built for the DVI-D Transmission in the single-link. Five control cores are under others, to transfer the DDC mode and the hardware detect.

Optimized shielding guarantees high transmission quality. Flexible cable optimized for Multi-Media applications.








| Article   | Picture  | Specification  | Type  |
|---|--|--|---|
| <p><b>VGA Connector, 15-pole HDD socket</b><br/>with screw connector, Halogen free and flame retardant<br/>Impedance of 75 Ohm, low damping factors<br/>Installation dimension: 25 x 50 mm</p>                                      |   | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p> | <p><b>9330 0810 0000</b></p> <p><b>9330 4040 0000</b></p> |
| <p>Fits profile:<br/>1,2,5,6</p>  |  |  |   |
| <p><b>VGA Connector, 15-pole HDD socket</b><br/>Angular outlet with label field<br/>with screw connector, Halogen free and flame retardant,<br/>Impedance of 75 Ohm, low damping factors<br/>Installation dimension: 50 x 50 mm</p> |   | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p> | <p><b>9330 2370 0000</b></p> <p><b>9330 4140 0000</b></p> |
| <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p>  |  |  |   |
| <p><b>DVI-A Connector, 9 + 5-pole, DVI socket (analog)</b><br/>low damping factors<br/>Cable Halogen free and flame retardant<br/>Installation dimension: 25 x 50 mm</p>  |  | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p>  | <p><b>9330 0860 0000</b></p> <p><b>9330 9700 0000</b></p> |
| <p>Fits profile:<br/>1,2,5,6</p>  |  |  |   |

\* Cable length measured from the position of the connection field inside the profile. Other cable lengths per meter on request.

# EVOLine® Multimedia Modules

| Article  | Picture | Specification  | Type                  |
|--|---------|--|-----------------------|
| <b>DVI-A Connector, 9 + 5-pole, DVI socket (analog)</b><br>Angular outlet with label field<br>low damping factors<br>Cable Halogen free and flame retardant<br>Installation dimension: 50 x 50 mm<br>Fits profile:<br>2,3,4,5,6,7,8,9                                      |         | with 3,0 m cable* and plug                                   | <b>9330 2420 0000</b> |
|  |         | Cable extension ordered separately<br>without solder splices | <b>9330 9710 0000</b> |
| <b>DVI-D Connector, 18-pole, DVI socket (digital) Single-Link</b><br>low damping factors<br>Cable Halogen free and flame retardant<br>Installation dimension: 25 x 50 mm<br><br>Fits profile:<br>1,2,5,6   |         | with 3,0 m cable* and plug                                   | <b>9330 0850 0000</b> |
|  |         | Cable extension ordered separately<br>without solder splices | <b>9330 9700 0000</b> |
| <b>DVI-D Connector, 18-pole, DVI socket (digital) Single-Link</b><br>Angular outlet with label field<br>low damping factors<br>Cable Halogen free and flame retardant<br>Installation dimension: 50 x 50 mm<br><br>Fits profile:<br>2,3,4,5,6,7,8,9                        |         | with 3,0 m cable * and plug                                  | <b>9330 2410 0000</b> |
|  |         | Cable extension ordered separately<br>without solder splices | <b>9330 9710 0000</b> |
| <b>HDMI 1.3 Connector, HDMI socket</b><br>with Gold plated contacts for connecting HDMI connector cable<br>optimal performance with high end Gold plated plug<br>Transmission length to ca. 25 m<br>Installation dimension: 25 x 50 mm<br><br>Fits profile:<br>1,2,5,6     |         | with 0,2 m cable* and socket                                 | <b>9330 6060 0000</b> |
|  |         | with 3,0 m cable* and plug                                   | <b>9330 6070 0000</b> |
|  |         | Cable extension ordered separately                           |                       |
| <b>HDMI 1.3 Connector, HDMI socket</b><br>Angular outlet with label field with Gold plated contacts<br>optimal performance with high end Gold plated plug<br>Transmission length to ca. 25 m<br>Installation dimension: 50 x 50 mm<br><br>Fits profile:<br>2,3,4,5,6,7,8,9 |         | with 0,2 m cable* and socket                                 | <b>9330 6080 0000</b> |
|  |         | with 3,0 m cable* and plug                                   | <b>9330 6090 0000</b> |
|  |         | Cable extension ordered separately                           |                       |

\* Cable length measured from the position of the connection field inside the profile. Other cable lengths per meter on request.





| Article   | Picture   | Specification  | Type  |
|---|---|--|---|
| <p><b>Video Connector, Composite Video (RCA) and S-Video (4-pole MINI-DIN) socket</b><br/>with high end Gold plated plug, 75 Ohm impedance at low damping factors<br/>Installation dimension: 25 x 50 mm</p> <p>Fits profile:<br/>1,2,5,6</p>   |    | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p> | <p>9330 0820 0000</p> <p>9330 4050 0000</p> |
| <p><b>Video Connector, Composite Video (RCA) and S-Video (4-pole MINI-DIN) socket</b><br/>Angular outlet with label field<br/>with high end Gold plated plug, 75 Ohm impedance at low damping factors<br/>Installation dimension: 50 x 50 mm</p> <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p> |    | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p> | <p>9330 2470 0000</p> <p>9330 4150 0000</p> |
| <p><b>Video Connector, Composite Video (RCA) socket</b><br/>with high end Gold plated plug, 75 Ohm impedance at low damping factors<br/>Installation dimension: 25 x 50 mm</p> <p>Fits profile:<br/>1,2,5,6</p>   |   | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p> | <p>9330 0890 0000</p> <p>9330 4070 0000</p> |
| <p><b>Video Connector, Composite Video (RCA) socket</b><br/>Angular outlet with label field<br/>with high end Gold plated plug, 75 Ohm impedance at low damping factors<br/>Installation dimension: 50 x 50 mm</p> <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p>                               |  | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p> | <p>9330 2480 0000</p> <p>9330 4170 0000</p> |
| <p><b>Video Connector, S-Video (4-pole MINI-DIN) socket</b><br/>with high end Gold plated plug, 75 Ohm impedance at low damping factors<br/>Installation dimension: 25 x 50 mm</p> <p>Fits profile:<br/>1,5,6</p>   |  | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p> | <p>9330 0900 0000</p> <p>9330 4060 0000</p> |

\* Cable length measured from the position of the connection field inside the profile. Other cable lengths per meter on request.

# EVOLine® Multimedia Modules

| Article  | Picture   | Specification   | Type  |
|--|---|---|---|
| <p><b>Video Connector, S-Video (4-pole MINI-DIN) socket</b><br/>Angular outlet with label field with high end Gold plated plug, 75 Ohm Impedance at low damping factors<br/>Installation dimension: 50 x 50 mm</p>                                 |    | <p>with 3,0 m cable* each and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p> | <p>9330 2490 0000</p> <p>9330 4160 0000</p> |
| <p><b>Video Connector, Component Video 3 x socket (RCA)</b><br/>Y, PB, PR, Green, Blue, Red<br/>75 Ohm impedance at low damping factors<br/>Installation dimension: 25 x 50 mm</p>   |    | <p>with 3,0 m cable* and plugs</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p>     | <p>9330 8010 0000</p> <p>9331 0510 0000</p> |
| <p><b>Video Connector, Component Video 3 x socket (RCA)</b><br/>Y, PB, PR, Green, Blue, Red<br/>Angular outlet with label field with high end Gold plated plug, 75 Ohm impedance at low damping factors<br/>Installation dimension: 50 x 50 mm</p> |   | <p>with 3,0 m cable* and plugs</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p>     | <p>9330 8020 0000</p> <p>9331 0520 0000</p> |
| <p><b>Audio Connector,</b><br/>1 x Stereo jack socket 3,5 mm with high end Gold plated plug<br/>Installation dimension: 25 x 50 mm</p>   |  | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p>      | <p>9330 0910 0000</p> <p>9330 4100 0000</p> |
| <p><b>Audio Connector,</b><br/>1 x Stereo jack socket 3,5 mm<br/>Angular outlet with label field with high end Gold plated plug<br/>Installation dimension: 50 x 50 mm</p>   |  | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p>      | <p>9330 2460 0000</p> <p>9330 4200 0000</p> |

\* Cable length measured from the position of the connection field inside the profile. Other cable lengths per meter on request.

| Article  | Picture   | Specification   | Type  |
|--|---|---|---|
| <p><b>Audio Connector,</b><br/><b>2 x Stereo jack socket 3,5 mm</b><br/>with high end Gold plated plug<br/>Installation dimension: 25 x 50 mm</p> <p>Fits profile:<br/>1,2,5,6</p>   |    | <p>with 3,0 m cable* each and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p> | <p><b>9330 0840 0000</b></p> <p><b>9330 4090 0000</b></p> |
| <p><b>Audio Connector,</b><br/><b>2 x Stereo jack socket 3,5 mm</b><br/>Angular outlet with label field<br/>with high end Gold plated plug<br/>Installation dimension: 50 x 50 mm</p> <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p> |    | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p>      | <p><b>9330 2450 0000</b></p> <p><b>9330 4190 0000</b></p> |
| <p><b>Audio Connector, professional,</b><br/><b>XLR socket wired symmetrically</b><br/>with high end Gold plated plug<br/>Installation dimension: 50 x 50 mm</p> <p>Fits profile:<br/>1,2,5,6</p>                              |   | <p>with 3,0 m cable * and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p>     | <p><b>9330 3880 0000</b></p> <p><b>9330 9820 0000</b></p> |
| <p><b>Audio Connector, professional,</b><br/><b>XLR socket wired symmetrically</b><br/>Angular<br/>with high end Gold plated plug<br/>Installation dimension: 75 x 50 mm</p> <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p>          |  | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p>      | <p><b>9330 6050 0000</b></p> <p><b>9330 9830 0000</b></p> |

\* Cable length measured from the position of the connection field inside the profile. Other cable lengths per meter on request.

# EVOLine® Multimedia Modules





| Article  | Picture   | Specification  | Type                             |
|--|---|--|----------------------------------|
| <p><b>Audio Connector,</b><br/> <b>Stereo 2 x RCA socket L / R</b><br/>                     with high end Gold plated plug<br/>                     Installation dimension: 25 x 50 mm</p>   |    | with 3,0 m cable* and plug<br>Cable extension ordered separately<br>without solder splices<br><b>Special version on request</b>          | 9330 0830 0000<br>9330 4080 0000 |
| <p>Fits profile:<br/>                     1,2,5,6</p>  |   |  |                                  |
| <p><b>Audio Connector,</b><br/> <b>Stereo 2 x RCA socket L / R</b><br/>                     Angular outlet with label field<br/>                     with high end Gold plated plug<br/>                     Installation dimension: 50 x 50 mm</p>  |    | with 3,0 m cable* and plug<br>Cable extension ordered separately<br>without solder splices<br><b>Special version on request</b>          | 9330 2440 0000<br>9330 4180 0000 |
| <p>Fits profile:<br/>                     2,3,4,5,6,7,8,9</p>  |   |  |                                  |
| <p><b>Serial Connector</b><br/> <b>D-SUB socket 9-pole,</b><br/>                     with screw connector, Halogen free<br/>                     and flame retardant,<br/>                     flexible connector cable<br/>                     Installation dimension: 25 x 50 mm</p>  |   | with 3,0 m cable* and socket<br>Cable extension ordered separately<br>without solder splices   | 9330 0870 0000<br>9330 4130 0000 |
| <p>Fits profile:<br/>                     1,2,5,6</p>  |   |  |                                  |
| <p><b>Serial Connector</b><br/> <b>D-SUB socket 9-pole,</b><br/>                     Angular outlet with label field<br/>                     with screw connector, Halogen free<br/>                     and flame retardant,<br/>                     flexible connector cable<br/>                     Installation dimension: 50 x 50 mm</p> |  | with 3,0 m cable* and socket<br>Cable extension ordered separately<br>without solder splices   | 9330 2390 0000<br>9330 4230 0000 |
| <p>Fits profile:<br/>                     2,3,4,5,6,7,8,9</p>  |   |  |                                  |
| <p><b>Data Connector</b><br/> <b>one USB Type A, socket</b><br/>                     to connect standard<br/>                     USB - devices<br/>                     Installation dimension: 25 x 50 mm</p>  |  | USB 2.0 with 3,0 m USB cable and plug<br>Type A<br>USB 3.0 with 3,0 m USB cable and plug<br>Type A<br>Cable extension ordered separately | 9330 1040 0000<br>9330 1450 0000 |
| <p>Fits profile:<br/>                     1,2,5,6</p>  |   |  |                                  |

\* Cable length measured from the position of the connection field inside the profile. Other cable lengths per meter on request.






| Article  | Picture   | Specification   | Type  |
|--|---|---|---|
| <p><b>Data Connector one USB Type A, socket</b><br/>Angular outlet with label field to connect standard USB - devices<br/>Installation dimension: 50 x 50 mm</p> <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p>  |    | <p>USB 2.0 with 3,0 m USB cable* and plug type A</p> <p>USB 3.0 with 3,0 m USB cable* and plug type A</p> <p>Cable extension ordered separately</p>   | <p>9330 2430 0000</p> <p>9331 1460 0000</p> |
| <p><b>Data Connector two USB Type A, sockets</b><br/>Angular outlet with label field to connect standard USB - devices<br/>Installation dimension: 50 x 50 mm</p> <p>Fits profile:<br/>3,4,5,6,7,8,9</p>   |    | <p>USB 2.0 with a 3,0 m USB cable* and plug type A</p> <p>USB 3.0 with a 3,0 m USB cable* and plug type A</p> <p>2 x Cable extension ordered separately</p>   | <p>9330 6170 0000</p> <p>9331 1470 0000</p> |
| <p><b>Data Connector three USB 2.0, Type A, socket</b><br/>Angular outlet with label field to connect standard USB - devices<br/>Installation dimension: 50 x 50 mm</p> <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p>   |   | <p>each with a 3,0 m USB cable* and plug Type A</p> <p>3 x Cable extension ordered separately</p>   | <p>9330 7460 0000</p>                       |
| <p><b>Data Connector 4-port USB active hub, USB 2.0</b><br/>Four USB inputs, one USB output<br/>All ports support high-speed (480Mbps), Full speed (12Mbps) and Low speed (1.5 Mbps),<br/>Meets the USB 2.0 specification.<br/>External power supply for active power to the connected USB devices.<br/>Supports Plug and Play and hot swap.<br/>Equipped with detection and protection against overvoltage<br/>Network connector Cable 1.3 m<br/>Operating Systems:<br/>Win 98/98SE/ME/2000 / XP/VISTA/MacOS8.6 and higher<br/>Installation dimension: 100 x 50 mm</p> <p>Fits profile:<br/>1</p> |  | <p>each with a 3,0 m USB cable* and plug Type A</p> <p>Cable extension ordered separately</p> <p><b>A guaranteed functionality of peripheral devices can not be guaranteed due to the large amount of individual suppliers.</b></p> | <p>9330 5950 0000</p>                       |

\* Cable length measured from the position of the connection field inside the profile. Other cable lengths per meter on request.

# EVOLine® Multimedia Modules

| Article  | Picture   | Specification   | Type  |
|--|---|---|---|
| <p><b>Data Connector</b><br/> <b>2 x 4-port USB active hub, USB 2.0</b><br/>           2 x four USB inputs, one USB output<br/>           All ports support high-speed (480 Mbps), Full Speed (12 Mbps) and Low Speed (1.5 Mbps), Meets The USB 2.0 specification.<br/>           2 x external power supply for active power of the connected USB devices.<br/>           Supports Plug and Play and Hot swap.<br/>           Equipped with detection and Protection against overvoltage<br/>           2 x power connector Cable 1.3 m<br/>           Operating Systems:<br/>           Win 98/98SE/ME/2000 / XP/VISTA/MacOS8.6 and higher<br/>           Installation dimension: 100 x 50 mm</p> |    | <p>each with a 3,0 m USB cable* and plug type A</p> <p>2 x cable extension ordered separately</p> <p><b>A guaranteed functionality of peripheral devices can not be guaranteed due to the large amount of individual suppliers.</b></p> | <p><b>9330 5960 0000</b></p>                              |
| <p>Fits profile:<br/>1</p>   |   |   |   |
| <p><b>VGA Audio Connector</b><br/> <b>VGA Connector, 15-pole HDD socket</b><br/>           with screw connector, Halogen free<br/>           75 Ohm impedance,<br/>           low damping factors<br/>           stereo jack socket 3,5 mm,<br/>           with high end Gold plated plug<br/>           Installation dimension: 25 x 50 mm</p>  |   | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p>  | <p><b>9330 7920 0000</b></p> <p><b>9330 1047 0000</b></p> |
| <p>Fits profile:<br/>1,2,5,6</p>   |   |   |   |
| <p><b>Audio-Video Connector,</b><br/> <b>stereo jack socket 3,5 mm,</b><br/> <b>S-Video (4-pole MINI-DIN) socket</b><br/>           Angular outlet with label field<br/>           with high end Gold plated plug,<br/>           75 Ohm impedance at low damping factors<br/>           Installation dimension: 50 x 50 mm</p>  |  | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p>  | <p><b>9330 6860 0000</b></p> <p><b>9330 1046 0000</b></p> |
| <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p>   |   |   |   |
| <p><b>Audio-Video Connector,</b><br/> <b>stereo jack socket 3,5 mm,</b><br/> <b>Composite Video (RCA) socket</b><br/>           with high end Gold plated plug,<br/>           75 Ohm impedance at low damping factors<br/>           Installation dimension: 25 x 50 mm</p>   |  | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p>  | <p><b>9330 6970 0000</b></p> <p><b>9330 1043 0000</b></p> |
| <p>Fits profile:<br/>1,2,5,6</p>   |   |   |   |

\* Cable length measured from the position of the connection field inside the profile. Other cable lengths per meter on request.

| Article  | Picture   | Specification  | Type  |
|--|---|--|---|
| <p><b>Audio-Video Connector, stereo jack socket 3,5 mm Composite Video (RCA) socket</b><br/>with high end Gold plated plug, 75 Ohm impedance at low damping factors<br/>Angular outlet with label field<br/>Installation dimension: 50 x 50 mm</p> <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p>  |    | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p>                         | <p>9330 6890 0000</p> <p>9330 1044 0000</p> |
| <p><b>Audio-Video Connector, stereo 2 x RCA socket L / R Composite Video (RCA) socket</b><br/>with high end Gold plated plug, 75 Ohm impedance at low damping factors<br/>Angular outlet with label field<br/>Installation dimension: 50 x 50 mm</p> <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p>  |    | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p>                         | <p>9330 7480 0000</p> <p>9331 0530 0000</p> |
| <p><b>Audio-Video Connector, Stereo 2 x RCA socket L / R S-Video (4-pole MINI-DIN) socket</b><br/>75 Ohm impedance at low damping factors<br/>Angular outlet with label field<br/>Installation dimension: 50 x 50 mm</p> <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p>  |   | <p>with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p> <p><b>Special version on request</b></p>                         | <p>9330 7930 0000</p> <p>9330 1045 0000</p> |
| <p><b>Audio-Connector with switch normally open, 1-pole Series 18, (eao)</b><br/>Switching capacity max. 42 VDC, 100 mA<br/>Lens size: 14 x 14 mm<br/>Lens colour: Grey<br/>Stereo jack socket 3.5 mm with high end Gold plated plug optimal performance<br/>Angular outlet with label field<br/>Installation dimension: 50 x 50 mm</p> <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p> |  | <p>Audio with 3,0 m cable* and plug</p> <p>Cable extension ordered separately</p> <p>without solder splices</p>  | <p>9331 0480 0000</p> <p>9331 0490 0000</p> |
| <p><b>Audio-Data Connector, Stereo Jack socket 3,5 mm with high end Gold plated plug Telephone-/data socket (Reichle Et De-Massari)</b><br/>Snap In<br/>Angular outlet with label field<br/>Installation dimension: 50 x 50 mm</p> <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p>  |  | <p>Audio and RJ45 CAT5e shielded, with 3,0 m Cable* and plug</p> <p>Audio and RJ45 CAT6 shielded, with 3,0 m Cable* and plug</p> <p>Cable extension ordered separately</p> | <p>9330 6360 0000</p> <p>9330 7610 0000</p> |






\* Cable length measured from the position of the connection field inside the profile. Other cable lengths per meter on request.

# EVOline® Multimedia Modules

| Article  | Picture   | Specification   | Type  |
|--|---|---|---|
| <p><b>Audio-Data Connector, Stereo jack socket 3,5 mm</b><br/>with high end Gold plated plug<br/><b>modular-adapter</b><br/>(Elbro)<br/>RJ45 on RJ45, 1:1 interconnected<br/>RJ45 CAT6 shielded<br/>Angular outlet with label field<br/>Installation dimension: 50 x 50 mm</p> |    | <p>Audio, with 3,0 m cable* and plug</p> <p>Cable extension ordered separately<br/>without solder splices</p> | <p><b>9330 7800 0000</b></p> <p><b>9331 0500 0000</b></p> |
| <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p>   |   |   |   |
| <p><b>TV Connector</b><br/>Coaxial 75 Ohm<br/>Shielding &gt; 90 dB<br/>Angular outlet with label field<br/>Installation dimension: 50 x 50 mm</p>  |    | <p>with 2,5 m cable* plug/socket</p>  | <b>9330 7590 0000</b>                                     |
| <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p>   |   |   |   |
| <p><b>TV-Radio Connector</b><br/>Coaxial 75 Ohm<br/>Shielding &gt; 90 dB<br/>Installation dimension: 50 x 50 mm</p> <p>TV = plug<br/>Radio = socket</p>  |   | <p>with 2,5 m cable* plug/socket</p>  | <b>9330 6320 0000</b>                                     |
| <p>Fits profile:<br/>1,2,5,6</p>   |   |   |   |
| <p><b>TV-Radio Connector</b><br/>Coaxial 75 Ohm<br/>Shielding &gt; 90 dB<br/>Angular outlet with label field<br/>Installation dimension: 50 x 50 mm</p> <p>TV = plug<br/>Radio = socket</p>  |  | <p>with 2,5 m cable* plug/socket</p>  | <b>9330 6330 0000</b>                                     |
| <p>Fits profile:<br/>2,3,4,5,6,7,8,9</p>   |   |   |   |

**Special combinations  
on request.**

\* Cable length measured from the position of the connection field inside the profile. Other cable lengths per meter on request.

| Article  | Picture   | Specification  | Type   |
|--|---|--|--|
| <p><b>FM Radio Module</b></p> <ul style="list-style-type: none"> <li>- UKW Radio mono with remote control</li> <li>- Autoscan function</li> <li>- Direct frequency input possible</li> <li>- 9 stations presetable</li> <li>- Confirmation beep (Optional: high / low / off) when pressed</li> <li>- Switch on operating voltage programmable</li> <li>- Operation indication via LED</li> <li>- 2 EVOLine® speaker modules connectable.</li> </ul> <p>Installation dimension: 150 x 50 mm<br/>Fits profile: 1,2,5,9</p> |    | <p>Technical data:<br/>Supply voltage: 230 V ~ / 50 Hz<br/>Output power: 1.3 W<br/>Frequency range: FM 87.5-108 MHz<br/>Frequency response: 40 Hz to 15 kHz<br/>Speaker impedance:&gt; 4 Ohm</p> | Black<br><b>9330 6430 0000</b>                               |
| <p><b>FM Radio Module</b></p> <ul style="list-style-type: none"> <li>- UKW Radio mono with Remote control</li> <li>- Autoscan function</li> <li>- Direct frequency input possible</li> <li>- 9 stations presetable</li> <li>- Confirmation beep (Optional: high / low / off) when pressed</li> <li>- Switch on operating voltage programmable</li> <li>- Operation indication via LED</li> <li>- 2 EVOLine® speaker modules connectable.</li> </ul> <p>Installation dimension: 150 x 50 mm<br/>Fits profile: 1,2,5,9</p> |    | <p>Technical data:<br/>Supply voltage: 230 V ~ / 50 Hz<br/>Output power: 1.3 W<br/>Frequency range: FM 87.5-108 MHz<br/>Frequency response: 40 Hz to 15 kHz<br/>Speaker impedance:&gt; 4 Ohm</p> | Stainless Steel lacquered (ALANOX®)<br><b>9330 8090 0000</b> |
| <p><b>Remote control supplied with FM radio module</b></p>   |   |  | Silver / Black   |
| <p><b>Speaker Module</b></p> <p>two full-range speakers with high efficiency and wide angle output for playback of voice and music in conjunction with iPod *, iPhone * and radio module<br/>Installation dimension: 100 x 50 mm</p>   |  | <p>Technical data:<br/>Power handling: 3 / 4 W<br/>Impedance: 8 Ohm<br/>Frequency response (-3 dB): 240-13 kHz<br/>Noise Level: 1W/1m: 79 dB at 3 W: 83 dB<br/>Resonance frequency: 260 Hz</p>   | Black<br><b>9330 6440 0000</b>                               |
| Fits profile: 1,2,5,9  |   |  |  |
| <p><b>Speaker Module</b></p> <p>two full-range speakers with high efficiency and wide angle output for playback of voice and music in conjunction with iPod *, iPhone * and radio module<br/>Installation dimension: 100 x 50 mm</p>   |  | <p>Technical data:<br/>Power handling: 3 / 4 W<br/>Impedance: 8 Ohm<br/>Frequency response (-3 dB): 240-13 kHz<br/>Noise Level: 1W/1m: 79 dB at 3 W: 83 dB<br/>Resonance frequency: 260 Hz</p>   | Stainless Steel lacquered (ALANOX®)<br><b>9330 8100 0000</b> |
| Fits profile: 1,2,5,9  |   |  |  |

\* TM Apple Computer, Inc.

# EVOLine® Multimedia Modules

## Article

### iPod® / iPhone® Module

- Stereo amplifier and charging function for portable music players from the Apple I-Series e.g. Apple iPod® and Apple iPhone®.
  - Integrated buttons for volume control and AUX on / off.
  - Built-in infrared receiver for optional remote control with features:
    - Volume, Play / Stop and Skip
  - AUX input with 3.5 mm mini-stereo jack for external audio source e.g. MP3 player.
  - Can be combined with the EVOLine® speaker modules or other high quality speakers (Not included).
  - With the optional stereo line-
    - Output can be configured for multiroom systems.
- Installation dimension: 75 x 50 mm

Fits profile: 1

## Picture



## Specification

Technical data:  
 Input voltage: 200 mV Line  
 Input impedance: 47 Ohm Line  
 Output voltage: max. 3,5 V  
 Output impedance: 8 Ohm  
 Power rating: 2 x 1,5 W  
 Operating voltage: 230 V ~

Black

## Type

9330 6450 0000

Optional:  
 Remote control  
 Stereo line-out output

Delivery without iPod®

### iPod® / iPhone® Module

- Stereo amplifier and charging function for portable music players from the Apple I-Series e.g. Apple iPod® and Apple iPhone®.
  - Integrated buttons for volume control and AUX on / off.
  - Built-in infrared receiver for optional remote control with Features:
    - Volume, Play / Stop and Skip
  - AUX input with 3.5 mm mini-Stereo jack for external audio source e.g. MP3 player.
  - Can be combined with the EVOLine® Speaker modules or other high quality speakers (Not included).
  - With the optional stereo line-
    - Output can be configured for multiroom systems.
- Installation dimension: 75 x 50 mm

Fits profile: 1



Technical data:  
 Input voltage: 200 mV Line  
 Input impedance: 47 Ohm Line  
 Output voltage: max. 3,5 V  
 Output impedance: 8 Ohm  
 Power rating: 2 x 1,5 W  
 Operating voltage: 230 V ~

Stainless Steel lacquered (ALANOX®)

9330 8110 0000

Optional:  
 Remote control  
 Stereo line-out output

Delivery without iPod®

### Remote control iPod® / iPhone® module

White



9331 0580 0000