





EVoline® Switch and Pushbutton Modules






Article	Picture	Specification	Type
<p><b>ON / OFF switch, 230 V~Blue illuminated</b> with lamp symbol for switching of external lighting installation dimensions: 50 x 50 mm</p>			<p>9330 6650 0000</p>
<p>Fits profile: 1,2,9</p>			<p>9330 6660 0000</p>
<p><b>ON / OFF switch, 230 V~Blue illuminated</b> with lamp symbol for switching of external lighting installation dimensions: 50 x 50 mm</p>			<p>9330 0010 0000</p>
<p>Fits profile: 3,5</p>			<p>9330 0010 0000</p>
<p><b>ON / OFF switch, 230 V~Blue illuminated</b> Installation dimensions: 50 x 50 mm Can be used for a variety of functions e.g. switching installed sockets, switching design lighting, switching external sources via power exit cable and more.</p>	<p>Fits profile: 1,2,3,4,5,6,7,8,9</p>		

# EVoline® Switch and Pushbutton Modules

Article	Picture	Specification	Type
<p><b>Pushbutton, 1-fold</b> as shutter, 1pole series 18, (eao) switching performance max. 42 V AC/DC, 100 mA size of pressure cap: 14 x 14 mm colour pressure cap: Grey installation dimensions: 25 x 50 mm</p> <p>Black</p> <p>Fits profile: 1,2,3,4,5,6,7,8,9</p>		with 3.0 m cable without plug	9330 6120 0000
<p><b>Pushbutton, 2-fold</b> as shutter, 1pole series 18, (eao) switching performance max. 42 V AC/DC, 100 mA size of pressure cap: 14 x 14 mm colour pressure cap: Grey installation dimensions: 25 x 50 mm</p> <p>Black</p> <p>Fits profile: 1,2,3,4,5,6,7,8,9</p>		with 3.0 m cable without plug	9330 6460 0000
<p><b>Pushbutton, 4-fold</b> as shutter, 1pole series 18, (eao) switching performance max. 42 V AC/DC, 100 mA size of pressure cap: 14 x 14 mm colour pressure cap: Grey installation dimensions: 50 x 50 mm</p> <p>Black</p> <p>Fits profile: 1,2,3,4,5,6,7,8,9</p>		with 3.0 m cable without plug	9330 6470 0000
<p><b>Pushbutton, 1-fold</b> as shutter, 1pole angular outlet with inscription field series 18, (eao) switching performance max. 42 V AC/DC, 100 mA size of pressure cap: 14 x 14 mm colour pressure cap: Grey installation dimensions: 50 x 50 mm</p> <p>Black</p> <p>Fits profile: 2,3,4,5,6,7,8,9</p>		with 3.0 m cable without plug	9330 7170 0000
<p><b>Pushbutton, 2-fold</b> as shutter, 1 pole angular outlet with inscription field series 18, (eao) switching performance max. 42 V AC/DC, 100 mA size of pressure cap: 14 x 14 mm colour pressure cap: Grey installation dimensions: 50 x 50 mm</p> <p>Black</p> <p>Fits profile: 2,3,4,5,6,7,8,9</p>		with 3.0 m cable without plug	9330 7180 0000

\* Cable length measured from the position of the connection field inside the profile. Other cable lengths per meter on request.

Article	Picture	Specification	Type
<p><b>Master/Slave Electronic</b> for switching of downstream sockets (slave sockets). Can be ordered only with upstream master and downstream slave socket (colours optional, see page 202), plastic plate: Black, installation dimensions: 75 x 50 mm</p> <p>Fits profile: 1,2,3,4,5,6,7,8,9</p>		<p>switching threshold: 20 up to 100 mA adjustable, nominal voltage: 250 V nominal current: 16 A Pole-number: 2 pole with earthing contact safety provision: IP20 Slave-switching: 2pole</p>	<p><b>9330 6160 0000</b></p>
<p><b>Emergency stop button with protection collar and imprint (eao) (EMERGENCY STOP)</b> overload safe EN IEC 60947-5-5 turn unlock clockwise illumination: LED Red illuminated, 12V DC external mushroom pressure cap: plastic Red elevated installation frontform: round installation dimensions: 50 x 50 mm</p> <p>Fits profile: 1,2,5,9</p>		<p>Contacts: 2 opener switching function: snap-in function switching system: push button switch power acceptance: 9.7 up to 12.4 mA switching performance: 250 V AC, 5 A</p> <p>with 3.0 m cable without plug</p>	<p><b>9330 6270 0000</b></p>
<p><b>Key holder with 2 keys</b> (eao) 2 Key positions Position A: basic Position C: snap-in function standard lock 1001 front: plastic Black installation: elevated installation frontform: round frontring: Aluminium nature installation dimensions: 50 x 50 mm</p> <p>Fits profile: 1,2,3,5,9</p>		<p>Key pull-out: position C + A switching function: snap-in function switching system: jumping switch element switching performance: 250 V AC, 5 A</p> <p>with 3.0 m cable without plug</p>	<p><b>9330 6280 0000</b></p>

\* Cable length measured from the position of the connection field inside the profile. Other cable lengths per meter on request.

